


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	15-0016	BROKE TOOLS OUT INTO SEPARATE DRAWINGS AND ADDED INDIVIDUAL T/N'S TO BOM FOR -1 RBW109-3130-84-109, -3 RBW109-3130-84-115, -5 RBW109-3130-84-103. -13 ADDED CUTOUT FOR -14. DELETED -5, -7, -9, -19, -21, -23, AND -25. ADDED -14, -16 AND -18.	1/20/15	RJC	JAG
2	06-0101	UPDATED TO NEW STANDARD. -1, -3, -5 REMOVED DASH No's. -16 & -18 REMOVED. -11 -13 -14 CH'D TOLERANCES WAS .XXX ± .005 IS .XXX ± .010, WAS .XX ± .01 IS .XX ± .03. -11 CH'D DIMS WAS 3.10 IS 3.60, WAS 2.00 IS 2.60. ADDED DIMS 4X .70, 4X 45°, -13 ADDED DIMS 4X .70, 4X 45°, 3.125, 1.750, .43. REMOVED DIM 4X R.68. -14 CH'D DIM WAS (.06) IS .06.	8/9/2016	DEW	SM





NOTE:
1. REF. AGUSTA T/N: 109-3130-84-101.
2. ATTACH PLACARD -17 TO OUTSIDE OF CASE.

DART AEROSPACE																	
TITLE T/R DRIVE SHAFT RING NUT REMOVE/INSTALL																	
DWG NO. RBW109-3130-84-101	REV 2																
<table border="1"> <tr> <td>MAT'L</td> <td>UNLESS OTHERWISE SPECIFIED</td> </tr> <tr> <td>TREAT</td> <td>DIMENSIONS ARE IN INCHES</td> </tr> <tr> <td>FINISH</td> <td>.XXX ± .005 FRACTIONS ± 1/8</td> </tr> <tr> <td>SPEC</td> <td>.XX ± .01 ANGLES ± 5°</td> </tr> <tr> <td></td> <td>.X ± .1 SURFACES = 125°</td> </tr> <tr> <td colspan="2">1. BREAK ALL SHARP EDGES .015 x 45° OR .015R</td> </tr> <tr> <td colspan="2">2. DIMENSIONAL LIMITS APPLY AFTER PLATING</td> </tr> <tr> <td colspan="2">3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009</td> </tr> </table>		MAT'L	UNLESS OTHERWISE SPECIFIED	TREAT	DIMENSIONS ARE IN INCHES	FINISH	.XXX ± .005 FRACTIONS ± 1/8	SPEC	.XX ± .01 ANGLES ± 5°		.X ± .1 SURFACES = 125°	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R		2. DIMENSIONAL LIMITS APPLY AFTER PLATING		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
MAT'L	UNLESS OTHERWISE SPECIFIED																
TREAT	DIMENSIONS ARE IN INCHES																
FINISH	.XXX ± .005 FRACTIONS ± 1/8																
SPEC	.XX ± .01 ANGLES ± 5°																
	.X ± .1 SURFACES = 125°																
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R																	
2. DIMENSIONAL LIMITS APPLY AFTER PLATING																	
3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009																	
<table border="1"> <tr> <td>DRAWN BY:</td> <td>GILBERT</td> </tr> <tr> <td>CHECKED:</td> <td>DUERFELDT</td> </tr> <tr> <td>OPPS APPR:</td> <td>ANDERSON</td> </tr> <tr> <td>QA APPR:</td> <td>LINDSAY</td> </tr> <tr> <td>APPROVED:</td> <td>MACKOVJAK</td> </tr> <tr> <td>SCALE</td> <td>1:6</td> </tr> <tr> <td>DATE</td> <td>5/21/2012</td> </tr> </table>		DRAWN BY:	GILBERT	CHECKED:	DUERFELDT	OPPS APPR:	ANDERSON	QA APPR:	LINDSAY	APPROVED:	MACKOVJAK	SCALE	1:6	DATE	5/21/2012		
DRAWN BY:	GILBERT																
CHECKED:	DUERFELDT																
OPPS APPR:	ANDERSON																
QA APPR:	LINDSAY																
APPROVED:	MACKOVJAK																
SCALE	1:6																
DATE	5/21/2012																
USED ON MODEL AW119																	
SHEET 1 OF 4																	

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
				1	REACTOR TOOL		RBW109-3130-84-109	1
				1	BASE		RBW109-3130-84-115	1
				1	WRENCH ASSY		RBW109-3130-84-103	1
		B/O	-11	1	BOTTOM FOAM	ETHAFOAM 220, BLACK	4-1/4 X 11-1/2 X 17 (CASE SOLUTIONS)	2
		B/O	-13	1	TOP TOOL CUSHION	ETHAFOAM 220, BLACK	1-3/4 X 11-1/2 X 17 (CASE SOLUTIONS)	3
			-14	1	TOOL PLACARD	PLASTIC		4
		B/O	-15	1	CASE	PLASTIC	PELICAN #APP-1500-E	N/S
		B/O		1	DART PLACARD	ALUMINUM	#RB41011	N/S

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
2	16-0101	-11 CH'D DIMS WAS $\nabla 3.10$ IS $\nabla 3.60$, WAS $\nabla 2.00$ IS $\nabla 2.60$, CH'D TOLERANCES WAS .XXX \pm .005 IS .XXX \pm .010, WAS .XX \pm .01 IS .XX \pm .03, ADDED DIMS 4X .70, 4X 45°, REMOVED DIM 4X R.68.	8/11/2016	DEW
APPROVED			SM	






(-11)
BOTTOM FOAM

DART AEROSPACE	
TITLE: T/R DRIVE SHAFT RING NUT REMOVE/INSTALL	
DWG NO.: RBW109-3130-84-101-11	REV: 2
MAT'L: ETHAFOAM 220, BLACK	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
.XXX \pm .010 FRACTIONS \pm 1/8	
.XX \pm .03 ANGLES \pm 1°	
.X \pm .1 SURFACES = 125/✓	
SPEC: 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: GILBERT	USED ON MODEL
CHECKED: DUERFELDT	AW119
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: MACKOVJAK	
SCALE: 1:4	DATE: 2/21/2012
SHEET 2 OF 4	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	15-0016	-13 ADDED CUTOUT FOR -14.	1/20/2015	RJC	JAG
2	16-0101	-13 CH'D TOLERANCES WAS .XXX ± .005 IS .XXX ± .010, WAS .XX ± .03 IS .XX ± .01. ADDED DIMS 4X .70, 4X 45°, 3.13, 1.75, 2X .43. REMOVED DIM 4X R.68.	8/9/2016	DEW	SM



(-13)



TOP TOOL CUSHION

DART AEROSPACE	
TITLE T/R DRIVE SHAFT RING NUT REMOVE/INSTALL	
DWG NO. RBW109-3130-84-101-13	REV 2
MAT'L ETHAFOAM 220, BLACK	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
.XXX ± .010 FRACTIONS ± 1/8	
.XX ± .03 ANGLES ± 1°	
.X ± .1 SURFACES = 125°	
SPEC 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: GILBERT	USED ON MODEL
CHECKED: DUERFELDT	AW119
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: MACKOVJAK	
SCALE 1:4	DATE 5/22/2012
SHEET 3 OF 4	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	15-0016	-14 ADDED PLACARD.	1/20/2015	RJC	JAG
2	16-0101	-14 CH'D TOLERANCES WAS .XXX ± .005 IS .XXX ± .010, WAS .XX ± .03 IS .XX ± .01. CH'D DIM WAS (.06) IS .06.	8/11/2016	DEW	SM

BLACK BACKGROUND
W/ WHITE LINES & LETTERS



NOTE:
USE PDF FOR PLACARD.

(-14)
TOOL PLACARD

DART AEROSPACE	
TITLE T/R DRIVE SHAFT RING NUT REMOVE/INSTALL	
DWG NO. RBW109-3130-84-101-14	REV 2
MAT'L PLASTIC	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125/
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES
CHECKED: DUERFELDT	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: MACKOVJAK	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
SCALE 1:1	DATE 1/20/2015
	USED ON MODEL AW119
	SHEET 4 OF 4